



WATERPROOF FAN (IP68)

JCD 60mm ~ 172mm / Thickness : min 25mm - max 51mm

*Noise is measured at the distance of 1 meter from the axis of intake. Specifications are subject to change without prior notice.

Bearing type: B=Ball F=Fluid

Option:    

	Frame size (mm)	Model No.	Bearing Type	Rated Voltage (VDC)	Current (A)	Power (W)	Rated Speed (RPM)	Maximum AirFlow (CMM)	Maximum AirFlow (CFM)	Maximum Pressure (InAq)	Maximum Pressure (mmAq)	*Noise Level (dB/A)	Weight (g)	
JCD08025-0D(Q68)	80x80x25	JCD0802512JB1A0D(Q68)	B	12	0.2	2.4	3500	1.35	47.5	0.14	3.56	35	82	
	80x80x25	JCD0802512IB1A0D(Q68)	B	12	0.32	3.84	4000	1.58	55.8	0.18	4.57	37	82	
	80x80x25	JCD0802512LB1A0D(Q68)	B	12	0.4	4.8	4500	1.88	66.4	0.22	5.59	42	82	
	80x80x25	JCD0802512MB1A0D(Q68)	B	12	0.65	7.8	5000	1.98	69.9	0.26	6.6	44	82	
	80x80x25	JCD0802512HB1A0D(Q68)	B	12	0.81	9.72	5500	2.1	74.3	0.27	6.86	46	82	
	80x80x25	JCD0802512UB1A0D(Q68)	B	12	1	12	6500	2.37	83.6	0.38	9.65	50	82	
	80x80x25	JCD0802524JB1A0D(Q68)	B	24	0.12	2.88	3500	1.35	47.5	0.14	3.56	35	82	
	80x80x25	JCD0802524IB1A0D(Q68)	B	24	0.16	3.84	4000	1.58	55.8	0.18	4.57	37	82	
	80x80x25	JCD0802524LB1A0D(Q68)	B	24	0.22	5.28	4500	1.88	66.4	0.22	5.59	42	82	
	80x80x25	JCD0802524MB1A0D(Q68)	B	24	0.32	7.68	5000	1.98	69.9	0.26	6.6	44	82	
	80x80x25	JCD0802524HB1A0D(Q68)	B	24	0.45	10.8	5500	2.1	74.3	0.27	6.86	46	82	
	80x80x25	JCD0802524UB1A0D(Q68)	B	24	0.51	12.24	6500	2.37	83.6	0.38	9.65	50	82	
	80x80x25	JCD0802548JB1A0D(Q68)	B	48	0.1	4.8	3500	1.35	47.5	0.14	3.56	35	82	
	80x80x25	JCD0802548IB1A0D(Q68)	B	48	0.15	7.2	4000	1.58	55.8	0.18	4.57	37	82	
	80x80x25	JCD0802548LB1A0D(Q68)	B	48	0.17	8.16	4500	1.88	66.4	0.22	5.59	42	82	
	80x80x25	JCD0802548MB1A0D(Q68)	B	48	0.19	9.12	5000	1.98	69.9	0.26	6.6	44	82	
	80x80x25	JCD0802548HB1A0D(Q68)	B	48	0.29	13.92	5500	2.1	74.3	0.27	6.86	46	82	
	80x80x25	JCD0802548UB1A0D(Q68)	B	48	0.6	28.8	6500	2.37	83.6	0.38	9.65	50	82	
	JCD08025-0E(Q68)	80x80x25	JCD0802505UB1A0E(Q68)	B	5	0.3	1.5	2700	0.9	31.8	0.11	2.79	29	80
		80x80x25	JCD0802512JB1A0E(Q68)	B	12	0.17	2.04	2700	0.9	31.8	0.11	2.79	29	80
80x80x25		JCD0802512LB1A0E(Q68)	B	12	0.19	2.28	3000	1	35.4	0.14	3.56	33	80	
80x80x25		JCD0802512MB1A0E(Q68)	B	12	0.23	2.76	3600	1.2	42.4	0.2	5.08	38	80	
80x80x25		JCD0802512HB1A0E(Q68)	B	12	0.32	3.84	4300	1.43	50.5	0.27	6.86	43	80	
80x80x25		JCD0802512UB1A0E(Q68)	B	12	0.5	6	5000	1.85	65.2	0.42	10.4	44	80	
80x80x25		JCD0802512VB1A0E(Q68)	B	12	0.65	7.8	5700	2.11	74.3	0.55	13.52	47	80	
80x80x25		JCD0802524JB1A0E(Q68)	B	24	0.08	1.92	2700	0.9	31.8	0.11	2.79	29	80	
80x80x25		JCD0802524LB1A0E(Q68)	B	24	0.11	2.64	3000	1	35.4	0.14	3.56	33	80	
80x80x25		JCD0802524MB1A0E(Q68)	B	24	0.16	3.84	3600	1.2	42.4	0.2	5.08	38	80	
80x80x25		JCD0802524HB1A0E(Q68)	B	24	0.23	5.52	4300	1.43	50.5	0.27	6.86	43	80	
80x80x25		JCD0802524UB1A0E(Q68)	B	24	0.25	6	5000	1.69	60	0.38	9.65	48	80	
80x80x25		JCD0802548MB1A0E(Q68)	B	48	0.06	2.88	3000	1	35.4	0.14	3.56	33	80	
80x80x25		JCD0802548HB1A0E(Q68)	B	48	0.09	4.32	3600	1.2	42.4	0.2	5.08	38	80	
80x80x25		JCD0802548UB1A0E(Q68)	B	48	0.2	9.6	4300	1.43	50.5	0.27	6.86	43	80	
80x80x25		JCD0802548VB1A0E(Q68)	B	48	0.21	10.08	5000	1.69	60	0.38	9.65	48	80	



WATERPROOF FAN (IP68)

JCD 60mm ~ 172mm / Thickness : min 25mm - max 51mm

*Noise is measured at the distance of 1 meter from the axis of intake. Specifications are subject to change without prior notice.

Bearing type: B=Ball F=Fluid

Option:    

	Frame size (mm)	Model No.	Bearing Type	Rated Voltage (VDC)	Current (A)	Power (W)	Rated Speed (RPM)	Maximum AirFlow (CMM) (CFM)	Maximum Pressure (InAq) (mmAq)	*Noise Level (dB/A)	Weight (g)
JCD08025-0C(Q68)	80x80x25	JCD0802512LB1A0C(Q68)	B	12	0.14	1.68	2700	0.98 34.6	0.12 3.05	28	85
	80x80x25	JCD0802512MB1A0C(Q68)	B	12	0.2	2.4	3000	1.09 38.5	0.17 4.32	31	85
	80x80x25	JCD0802512HB1A0C(Q68)	B	12	0.24	2.88	3600	1.54 54.3	0.28 7.11	36	85
	80x80x25	JCD0802512UB1A0C(Q68)	B	12	0.44	5.28	4300	1.73 61.2	0.32 8.13	40	85
	80x80x25	JCD0802524JB1A0C(Q68)	B	24	0.08	1.92	2700	0.98 34.6	0.12 3.05	28	85
	80x80x25	JCD0802524LB1A0C(Q68)	B	24	0.11	2.64	3000	1.09 38.5	0.17 4.32	31	85
	80x80x25	JCD0802524MB1A0C(Q68)	B	24	0.15	3.6	3600	1.54 54.3	0.28 7.11	36	85
	80x80x25	JCD0802524HB1A0C(Q68)	B	24	0.2	4.8	4300	1.73 61.2	0.32 8.13	40	85
	80x80x25	JCD0802548JB1A0C(Q68)	B	48	0.05	2.4	2700	0.98 34.6	0.12 3.05	28	85
	80x80x25	JCD0802548LB1A0C(Q68)	B	48	0.07	3.36	3000	1.09 38.5	0.17 4.32	31	85
	80x80x25	JCD0802548MB1A0C(Q68)	B	48	0.1	4.8	3600	1.54 54.3	0.28 7.11	36	85
	80x80x25	JCD0802548HB1A0C(Q68)	B	48	0.14	6.72	4300	1.73 61.2	0.32 8.13	40	85