

Thermal Cycling Thermoelectric Modules



A product specially designed to cope with high-speed temperature cycles, providing longer life under the same temperature cycle conditions. Mainly used in PCR and analyzers.



P/N	I max (A)	U max (V)	ΔT Max (°C)	QC Max (W)	Dimension (mm)
TECT-01708	8.70	1.90	70	10.10	15*15*3
TECT-01714	14.00	2.10	71	16.10	22*22*5
TECT-03108	8.70	3.50	70	18.20	20*20*3
TECT-03114	14.00	3.75	71	29.30	30*30*5
TECT-04909	9.00	5.90	71	29.70	36*36*6
TECT-04914	14.00	5.90	71	46.20	36*36*5
TECT-06308	8.70	7.10	70	37.00	20*40*3
TECT-07108	8.70	8.00	70	41.70	30*30*3
TECT-07109	9.00	8.60	71	43.10	44*44*6
TECT-07114	14.00	8.60	71	67.00	44*44*5
TECT-12708	8.70	14.40	70	74.60	40*40*4
TECT-12711	11.40	14.40	71	97.10	50*50*5
TECT-12714	14.00	15.40	71	120.00	62*62*5
TECT-12715	15.40	14.40	71	132.10	50*50*4
TECT-12717	17.00	14.40	71	144.70	50*50*4
TECT-16108	8.70	18.20	70	94.60	40*40*4
TECT-19908	8.70	22.50	70	117.00	40*40*4

We keep the world cool™
www.jarothermal.com